



60W/120W

Description & Feature

This compact mixing amplifier is designed as convenient solution for small PA installations with USB player,Bluetooth and FM tuner receiver in a compact housing.

And this amplifier features two unbalanced microphone inputs and two AUX inputs,moreover the MIC1 has "VOICE PRIORITY" over the other inputs except of the alarm input, moreover a group of line level output is available for adding additional amplifier.

Equipped with step-up transformer to be best suitable for any 70-volt or 100-volt line public address system,in the same time 4~16 Ohm output load is also provided.

Level controllers include individual volume controller for inputs,master volume controller for all,BASS and TREBLE tone controllers.

Complete protection is provided for over temperature,over voltage,over load and short circuit speaker line conditions.

- ※ Built-in music streaming media including USB player,FM tuner and Bluetooth receiver.
- ※ 70/100-volt and 4~16 ohms(Ω) output loads.
- ※ Two microphone (MIC1 & MIC2) jacks,MIC2 supports 48V Phantom Power with switch ON/OFF.
- ※ EMC input has priority over the other inputs.
- ※ SMT circuit boards with highly stable performance.
- ※ High-definition display for the working status of playing programme.
- ※ Individual volume controller for inputs,and master volume controller for all.
- ※ BASS and TREBLE tone controllers.
- ※ Power supply AC100-240V and DC24V.
- ※ Protection provided for output short circuit,overload,high temperature,peak current limiters.

Specification

| Model | RH60PM | RH120PM |
|---------------------|---|---------|
| Rated Power | 60W | 120W |
| Speaker Output Mode | Low impedance:4-16 ohms (Ω) | |
| | Voltage line:70V & 100V | |
| Compatible Media | USB,SD,Bluetooth,FM,Aux In | |
| Playable Formats | MP3,WMA,WAV,FLAC,APE | |
| Bluetooth Name | BGM SYSTEM | |
| Bluetooth Frequency | 2402~2480 MHz | |
| Bluetooth E.I.R.P | 2 dBm | |
| FM Tuner Frequency | 87.50~107.50 MHz | |
| Frequency Response | 60 Hz ~ 15k Hz (\pm 3 dB) | |
| T.H.D | <1% at 1kHz,1/3 rated power | |
| S/N | \geq 75dB | |
| Tone Control | BASS:100 Hz (\pm 10 dB) , TREBLE:10k Hz (\pm 10 dB) | |
| Protection | Short circuit,overload,high temperature | |
| AC Power Supply | AC100V~230V / 50Hz, 0.33A | |
| AC Fuse | T3.15A | |
| DC Power Supply | DC24V, 3.13A | |
| Power Cord | $(3 \times 0.75 \text{ mm}^2) \times 1.5\text{M}$ | |
| Dimension | 71(H) \times 300(W) \times 191(D) mm | |
| Carton Size | 120(H) \times 350(W) \times 255(D) mm | |
| Net Weight | 4.90kg | 5.50kg |
| Gross Weight | 5.60kg | 6.10kg |